

5-TELJELISED TÖÖLEMISKESKUSED (trunnion)



	VM10Ui	VM10UHSi	VMX30USi	VMX30UHSi	VTXUi	BX40Ui	VMX60Ui
Mõõtmed	Ø 198mm / 150 Kg	Ø 198mm / 150 Kg	Ø 248mm / 200 Kg	Ø 248mm / 200 Kg	610x530mm/ 400 Kg	Ø 348mm / 250 Kg	Ø 500mm / 500 Kg
X/Y/Z telje käik	X/Y/Z - 533 x 406 x 483 mm	X/Y/Z - 533 x 406 x 483 mm	X/Y/Z - 762 x 508 x 520 mm	X/Y/Z - 762 x 508 x 520 mm	X/Y/Z - 1524 x 660 x 520 mm	X/Y/Z - 950 x 550 x 500 mm	X/Y/Z - 1524 x 660 x 520 mm
Tööriistahoidjad	BT30 20 positsiooni	BT30 20 positsiooni	BT40 40 positsiooni	HSK63 40 positsiooni	CAT / BT40 40 positsiooni	HSK 63 30 positsiooni	CAT / BT40 40 positsiooni
Spindel	11 KW / Max 10.000RPM	8 KW / Max 20.000RPM	18 KW / Max 18.000RPM	18 KW /Max 18.000RPM	18 KW / Max 12.000RPM	36 KW / Max 18.000RPM	18 KW /Max 12.000RPM
Kiirliikumine X/Y/Z	24 / 24 / 24 m/min	24 / 24 / 24 m/min	45 / 45 / 40 m/min	45 / 45 / 40 m/min	35 / 35 / 35 m/min	39 / 39 / 39 m/min	30 / 30 / 20 m/min
Kaal	2800 Kg	2800 Kg	5280 Kg	5280 Kg	12500 Kg	9400 Kg	6350 Kg